

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: 832FX-B

· Other Means of Identification: Black Flexible Epoxy Encapsulating and Potting Compound (Part B)

· Related Part Number:

832FX-B, 832FX-B-450ML, 832FX-B-1.7L, 832FX-B-7.4L, 832FX-B-40L, 832FX-B-360L

· UFI: EXF0-X0R7-J006-GHUN

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Application of the substance / the mixture Epoxy Hardener

· Uses advised against Not applicable

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

MG Chemicals Ltd. (Head Office)
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA
+(1) 905-331-1396
info@mgchemicals.com

MG Chemicals
Heame House, 23 Bliston Street
Sedgely Dudley DY3 1JA.
United Kingdom
+(44) 1663 362888

MG Chemicalst Ltd.
Level 2, Vision Exchange, Building Territorials Street,
Zone 1, Central Business, District,
Birkirkara CBD 1070,
MALTA

· Further information obtainable from: sds@mgchemicals.com

· 1.4 Emergency telephone number:

Members of the public seeking specific information on poisons should contact:

In England and Wales: NHS 111 - dial 111

In Scotland: NHS 24 - dial 111

Verisk 3E (Access code: 335388)

+(44) 20 3514787

+(1) 760 476 3961

UK Toll free: +(0) 800 680 0425

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008



GHS08 health hazard

STOT RE 2

H373 May cause damage to the liver, the immune system and the gastro-intestinal tract through prolonged or repeated exposure.

(Contd. on page 2)

— GB —

Trade name: 832FX-B

(Contd. of page 1)



GHS05 corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.



GHS09 environment

Aquatic Acute 1 H400 Very toxic to aquatic life.
Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.
Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS05



GHS07



GHS08



GHS09

Signal word Danger

Hazard-determining components of labelling:

polyoxypropylene diamine
Amines, coco alkyl
trimethylhexane-1,6-diamine

Hazard statements

H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H373 May cause damage to the liver, the immune system and the gastro-intestinal tract through prolonged or repeated exposure.
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.
P260 Do not breathe fumes, mist or vapours.
P280 Wear protective gloves, protective clothing, and eye protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/doctor.
P501 Dispose of contents and container in accordance with local, regional, and national regulations.

(Contd. on page 3)

GB

Trade name: 832FX-B

(Contd. of page 2)

- **2.3 Other hazards**
 - **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.

· Determination of endocrine-disrupting properties		
61788-44-1	phenol, styrenated	List II

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
 - **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 9046-10-0	polyoxypropylene diamine ⚠ Skin Corr. 1A, H314; Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302	59.0%
CAS: 61788-44-1	phenol, styrenated Substance identified as having endocrine disrupting properties (II)	20.0%
CAS: 25620-58-0 EINECS: 247-134-8	trimethylhexane-1,6-diamine ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Skin Sens. 1, H317; Aquatic Chronic 3, H412	9.0%
CAS: 61788-46-3 EINECS: 262-977-1 Index number: 612-285-00-4	Amines, coco alkyl ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Skin Corr. 1B, H314; ⚠ Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10); ⚠ Acute Tox. 4, H302; STOT SE 3, H335	9.0%
CAS: 90-72-2 EINECS: 202-013-9 Index number: 603-069-00-0	2,4,6-tris(dimethylaminomethyl)phenol ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	2.0%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
 - **General information:**

Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
 - **After inhalation:**

In case of unconsciousness place patient stably in side position for transportation.
Seek immediate medical advice.
Remove person to fresh air and keep comfortable for breathing.
If feeling unwell: Call a POISON CENTRE or doctor.
 - **After skin contact:**

Take off immediately all contaminated clothing. Wash with plenty of water or shower.
Immediately call a POISON CENTRE or doctor.
Wash contaminated clothing before reuse.
If skin irritation or rash occurs: Get medical advice or attention.
 - **After eye contact:**

Rinse cautiously with water for at least 30 minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Immediately call a POISON CENTER or doctor.

(Contd. on page 4)

Trade name: 832FX-B

(Contd. of page 3)

- **After swallowing:**
Rinse mouth.
Do NOT induce vomiting.
If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
 - **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
Not flammable or combustible, but burns if involved in a fire. Produces irritating smoke of unknown toxicity in fires.
Prevent fire-fighting wash from entering waterway or sewer system.
 - **Hazardous combustion products:**
Carbon Oxides (COx)
Nitrogen Oxides (NOx)
- **5.3 Advice for firefighters**
 - **Protective equipment:** Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Do not breathe fumes, mist or vapors.
- **6.2 Environmental precautions:**
Avoid release to the environment.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Use neutralising agent.
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Collect liquid in a sealable, chemical-resistant container.
Wash residue with a paper towel and place dirty towels in container.
Use soap and water to remove the last traces of residue.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

— GB —
(Contd. on page 5)

Trade name: 832FX-B

(Contd. of page 4)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

- Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- Wear protective gloves and eye protection.
- Wash hands and exposed skin thoroughly after handling.
- Take off contaminated clothing and wash it before reuse.
- Collect spillage.
- Contaminated work clothing should not be allowed out of the workplace.
- Do not breathe mist, vapours, spray.

- **Information about fire - and explosion protection:** Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

- **Requirements to be met by storerooms and receptacles:**
 - Keep in a dry and clean area, away from incompatible substances
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 - Keep container tightly sealed.
 - Store locked up.

· 7.3 Specific end use(s) See section 1.2

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· Additional information:

- The lists valid during the making were used as basis.
- Refer to the national or regional occupational exposure limit regulation for abbreviations and acronyms.

· 8.2 Exposure controls

· Appropriate engineering controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes and skin.

· Respiratory protection:

- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- Advice should be sought from respiratory protection specialists.
- If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.

· Hand protection

- Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 6)

Trade name: 832FX-B

(Contd. of page 5)



Protective gloves: EN374

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**



Safety glasses or tightly sealed goggles: EN 166

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· Physical state	Liquid
· Form:	Viscous
· Colour:	Amber coloured
· Odour:	Ammonia-like
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	>230 °C
· Flammability	Non flammable
· Lower and upper explosion limit	
· Lower:	Not applicable
· Upper:	Not applicable
· Flash point:	>104 °C
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic at 25 °C:	165 cP
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Relative density at 25 °C:	0.98
· Vapour density (air=1):	Not determined.
· Particle characteristics	Not applicable.

(Contd. on page 7)

— GB —

Trade name: 832FX-B

(Contd. of page 6)

· **9.2 Other information**

· **9.2.1 Information with regard to physical hazard classes**

Not applicable

· **9.2.2 Other safety characteristics**

· **Evaporation rate**

Not determined.

· **Ignition temperature:**

Product is not selfigniting.

· **Explosive properties:**

Product does not present an explosion hazard.

· **Solvent content:**

· **Organic solvents:**

Not available

· **VOC (EC)**

0.00 %

· **Solids content:**

1.0 %

SECTION 10: Stability and reactivity

· **10.1 Reactivity** Reacts exothermically with epoxide groups.

· **10.2 Chemical stability** Chemically stable at normal temperatures and pressures.

· **Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

· **10.3 Possibility of hazardous reactions** No dangerous reactions known.

· **10.4 Conditions to avoid**

Avoid open flames, excessive heat, sparks, ignition sources, and incompatible substances.

· **10.5 Incompatible materials:**

Strong oxidizing agents

Strong acids

· **10.6 Hazardous decomposition products:**

No dangerous decomposition products known.

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

· **Acute toxicity** Harmful if swallowed.

· **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Oral | LD50 | 667 mg/kg

9046-10-0 polyoxypropylene diamine

Oral | LD50 | 500 mg/kg (ATE)

25620-58-0 trimethylhexane-1,6-diamine

Oral | LD50 | 900 mg/kg (rat)

61788-46-3 Amines, coco alkyl

Oral | LD50 | 500 mg/kg (ATE)

90-72-2 2,4,6-tris(dimethylaminomethyl)phenol

Oral | LD50 | 500 mg/kg (ATE)

(Contd. on page 8)

— GB —

Trade name: 832FX-B

(Contd. of page 7)

- **Primary irritant effect:**
 - **Skin corrosion/irritation** Causes severe skin burns and eye damage.
 - **Serious eye damage/irritation** Causes serious eye damage.
 - **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure**
May cause damage to the liver, the immune system and the gastro-intestinal tract through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Summary of Effects and Symptoms by Routes of Exposure**
 - **Eyes:**
eye damage, pain
redness, serious irritation
burns
 - **Skin:**
chemical burns
blistering
redness, irritation
rash, allergic contact dermatitis
 - **Inhalation:** irritation of the respiratory tract
 - **Swallowed:**
irritation
abdominal pain
burning sensation
nausea, vomiting
- **Additional toxicological information:**
 - **Delayed and immediate effects as well as chronic effects from short and long-term exposure**
Prolonged and repeated exposure to uncured epoxy hardener may lead to skin sensitization.

· **11.2 Information on other hazards**

· Endocrine disrupting properties		
61788-44-1	phenol, styrenated	List II

SECTION 12: Ecological information

- **12.1 Toxicity**
 - **Aquatic toxicity:**
Very toxic to aquatic life with long lasting effect.
Avoid release to the environment.
Collect spillage.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.

(Contd. on page 9)

Trade name: 832FX-B

(Contd. of page 8)

- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
 - **Remark:** Very toxic for fish
 - **Additional ecological information:**
 - **General notes:**

Also poisonous for fish and plankton in water bodies.
Very toxic for aquatic organisms
Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Must not reach sewage water or drainage ditch undiluted or unneutralised.
Danger to drinking water if even extremely small quantities leak into the ground.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
 - **Recommendation** This material and its container must be disposed of as hazardous waste.

· European waste catalogue	
HP6	Acute Toxicity
HP8	Corrosive
HP14	Ecotoxic

- **Uncleaned packaging:**
 - **Recommendation:**

Containers may still present a chemical hazard/ danger when empty.
Dispose of contents in accordance with all local, regional, national, and international regulations.
Where possible retain label warnings and SDS and observe all notices pertaining to the product.

* SECTION 14: Transport information

· 14.1 UN number or ID number	
· ADR, IMDG, IATA	UN2735
· 14.2 UN proper shipping name	
· ADR, IMDG	AMINES, LIQUID, CORROSIVE, N.O.S. (trimethylhexane-1,6-diamine, polyoxypropylene diamine)
· IATA	Amines, liquid, corrosive, n.o.s. (trimethylhexane-1,6-diamine, polyoxypropylene diamine)
· 14.3 Transport hazard class(es)	
· ADR, IMDG, IATA	
	
· Class	8 Corrosive substances.
· Label	8

(Contd. on page 10)

Trade name: 832FX-B

(Contd. of page 9)

· 14.4 Packing group · ADR, IMDG, IATA		II
· 14.5 Environmental hazards: · Marine pollutant: · Special marking (ADR): · Special marking (IATA):		Product contains environmentally hazardous substances: Amines, coco alkyl MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS ENVIRONMENTALLY HAZARDOUS
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Segregation groups · Stowage Category · Segregation Code		Not applicable. 80 F-A,S-B (SGG18) Alkalis A SG35 Stow "separated from" SGG1-acids
· 14.7 Maritime transport in bulk according to IMO instruments		Not applicable.
· Transport/Additional information:  Limited Quantity 832FX-450ML, 832FX-1.7L		
· ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category · Tunnel restriction code		1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml 2 E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)		1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":		UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (TRIMETHYLHEXANE-1,6-DIAMINE, POLYOXYPROPYLENE DIAMINE), 8, II

— GB —

(Contd. on page 11)

Trade name: 832FX-B

(Contd. of page 10)

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act

· Regulated explosives precursors (Part 1)
None of the ingredients is listed.
· Regulated poisons (Part 2)
None of the ingredients is listed.
· Reportable explosives precursors (Part 3)
None of the ingredients is listed.
· Reportable poisons (Part 4)
None of the ingredients is listed.

· Directive 2012/18/EU

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category E1** Hazardous to the Aquatic Environment
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 100 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 200 t

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II
None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008	
Acute toxicity - oral Skin corrosion/irritation Serious eye damage/irritation Skin sensitisation Specific target organ toxicity (repeated exposure) Hazardous to the aquatic environment - short-term (acute) aquatic hazard Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

(Contd. on page 12)

Trade name: 832FX-B

(Contd. of page 11)

- **Department issuing SDS:** Regulatory department
- **Contact:** sds@mgchemicals.com
- **Date of previous version:** 04.06.2024
- **Version number of previous version:** 6.00
- **Abbreviations and acronyms:**
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - VOC: Volatile Organic Compounds (USA, EU)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - ATE: Acute toxicity estimate values
 - Acute Tox. 4: Acute toxicity – Category 4
 - Skin Corr. 1A: Skin corrosion/irritation – Category 1A
 - Skin Corr. 1B: Skin corrosion/irritation – Category 1B
 - Skin Irrit. 2: Skin corrosion/irritation – Category 2
 - Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 - Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 - Skin Sens. 1: Skin sensitisation – Category 1
 - STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 - STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
 - Asp. Tox. 1: Aspiration hazard – Category 1
 - Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
 - Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
 - Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
- *** Data compared to the previous version altered.**

— GB —