

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: 832FXT-B

· Other Means of Identification: Flexible Epoxy Resin

· Related Part Number:

832FXT-Part B, 832FXT-25ML (B), 832FXT-50ML (B), 832FXT-400ML (B), 832FXT-7.4L (B), 832FXT-40L (B)

· UFI: DYS0-50GP-D003-WG16

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Application of the substance / the mixture Epoxy Hardener

· Uses advised against Not for use as a spray coating

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

MG Chemicals Ltd. (Head Office)
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA
+(1) 905-331-1396
info@mgchemicals.com

MG Chemicals
Heame House, 23 Bliston Street
Sedgely Dudley DY3 1JA.
United Kingdom
+(44) 1663 362888

MG Chemicalst Ltd.
18-20, Msida Road,
Gzira, GZR 1401
MALTA

· Further information obtainable from: sds@mgchemicals.com

· 1.4 Emergency telephone number:

3E (Access code: 335388)
+(44) 20 3514787
+(1) 760 476 3961
UK Toll free: +(0) 800 680 0425

Members of the public seeking specific information on poisons should contact:
In England and Wales: NHS 111 - dial 111
In Scotland: NHS 24 - dial 111

* SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Skin Corr. 1B	H314 Causes severe skin burns and eye damage.
Eye Dam. 1	H318 Causes serious eye damage.
Skin Sens. 1	H317 May cause an allergic skin reaction.

(Contd. on page 2)

Safety data sheet

according to UK REACH

Page 2/12

Printing date 23.07.2025

Version number 1.00

Revision: 23.06.2025

Trade name: 832FXT-B

(Contd. of page 1)

STOT RE 2 H373 May cause damage to the liver, the immune system and the gastro-intestinal tract through prolonged or repeated exposure.
 Aquatic Acute 1 H400 Very toxic to aquatic life.
 Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



Signal word Danger

Hazard-determining components of labelling:

polyoxypropylene diamine
 phenol, styrenated
 Amines, coco alkyl
 trimethylhexane-1,6-diamine

Hazard statements

H314 Causes severe skin burns and eye damage.
 H317 May cause an allergic skin reaction.
 H373 May cause damage to the liver, the immune system and the gastro-intestinal tract through prolonged or repeated exposure.
 H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.
 P260 Do not breathe fumes, mist or vapours.
 P280 Wear protective gloves, protective clothing, and eye protection or face protection.
 P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER/doctor.

2.3 Other hazards

Results of PBT and vPvB assessment

- PBT: Not applicable.
- vPvB: Not applicable.

Determination of endocrine-disrupting properties

61788-44-1 phenol, styrenated

List II

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

— GB —

Safety data sheet

according to UK REACH

Page 3/12

Printing date 23.07.2025

Version number 1.00

Revision: 23.06.2025

Trade name: 832FXT-B

(Contd. of page 2)

· Dangerous components:		
CAS: 9046-10-0	polyoxypropylene diamine ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Chronic 3, H412	55%
CAS: 61788-44-1	phenol, styrenated Substance identified as having endocrine disrupting properties (II)	22%
CAS: 25620-58-0 EINECS: 247-134-8	trimethylhexane-1,6-diamine ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302; Skin Sens. 1, H317; Aquatic Chronic 3, H412	10%
CAS: 61788-46-3 EINECS: 262-977-1 Index number: 612-285-00-4	Amines, coco alkyl ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Skin Corr. 1B, H314; ⚠ Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=10); ⚠ Acute Tox. 4, H302; STOT SE 3, H335	10%
CAS: 90-72-2 EINECS: 202-013-9 Index number: 603-069-00-0	2,4,6-tris(dimethylaminomethyl)phenol ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	2%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Remove person to fresh air and keep comfortable for breathing.

Immediately call a POISON CENTER or doctor.

· **After skin contact:**

Take off immediately all contaminated clothing. Wash with plenty of water or shower.

Immediately call a POISON CENTRE or doctor.

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice or attention.

· **After eye contact:**

Rinse cautiously with water for at least 30 minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a POISON CENTER or doctor.

· **After swallowing:**

Rinse mouth. Do not induce vomiting.

Immediately call a POISON CENTER or doctor.

· **Information for doctor:** Treat symptomatically

· 4.2 Most important symptoms and effects, both acute and delayed

See section 11 for additional information.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

— GB —

(Contd. on page 4)

Safety data sheet according to UK REACH

Page 4/12

Printing date 23.07.2025

Version number 1.00

Revision: 23.06.2025

Trade name: 832FXT-B

(Contd. of page 3)

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.

· 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

Not flammable or combustible, but burns if involved in a fire. Produces irritating smoke of unknown toxicity in fires.

Prevent fire-fighting wash from entering waterway or sewer system.

Inhalation of toxic smoke during fire may have delayed effects. Exposed person may need to be put under surveillance for 48 h.

- **Hazardous combustion products:**

Carbon Oxides (COx)

Nitrogen Oxides (NOx)

· 5.3 Advice for firefighters

- **Protective equipment:** Wear self-contained breathing apparatus and full fire-fighting turn-out gear.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Remove or keep away all sources of extreme heat or open flames.

Do not breathe fumes, mist or vapors.

· 6.2 Environmental precautions:

Avoid release to the environment.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Collect liquid in a sealable, chemical-resistant container.

Wash residue with a paper towel and place dirty towels in container.

Use soap and water to remove the last traces of residue.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

* SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Prevent formation of aerosols.

Wear protective gloves and eye protection.

Wash hands and exposed skin thoroughly after handling.

Take off contaminated clothing and wash it before reuse.

Collect spillage.

Contaminated work clothing should not be allowed out of the workplace.

Do not breathe mist, vapours, spray.

Do not eat, drink, or smoke when using this product.

(Contd. on page 5)

— GB —

Safety data sheet according to UK REACH

Page 5/12

Printing date 23.07.2025

Version number 1.00

Revision: 23.06.2025

Trade name: 832FXT-B

(Contd. of page 4)

- **Information about fire - and explosion protection:** Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
 - **Storage:**
 - **Requirements to be met by storerooms and receptacles:**
Keep in a dry and clean area, away from incompatible substances
 - **Information about storage in one common storage facility:** Not required.
 - **Further information about storage conditions:**
Keep container tightly sealed.
Store locked up.
 - **Storage class:** 8 A
- **7.3 Specific end use(s)** See section 1.2

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**
 - **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
 - **Additional information:**
The lists valid during the making were used as basis.
Refer to the national or regional occupational exposure limit regulation for abbreviations and acronyms.
- **8.2 Exposure controls**
 - **Appropriate engineering controls** Keep airborne concentrations below exposure limits.
 - **Individual protection measures, such as personal protective equipment**
 - **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.
 - **Respiratory protection:**
Advice should be sought from respiratory protection specialists.
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
If the product is heated or worker has a known allergic reaction, consider using a full mask with organic vapor cartridge or with an independent air supply.
 - **Hand protection**



Protective gloves: EN374

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

— GB —

Safety data sheet according to UK REACH

Page 6/12

Printing date 23.07.2025

Version number 1.00

Revision: 23.06.2025

Trade name: 832FXT-B

(Contd. of page 5)

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye/face protection**



Safety glasses or tightly sealed goggles: EN 166

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· Physical state	Liquid
· Form:	Highly viscous
· Colour:	Amber coloured
· Odour:	Amine-like
· Odour threshold:	Not available
· Boiling point or initial boiling point and boiling range	>130 °C
· Flammability	Non flammable
· Lower and upper explosion limit	
· Lower:	Not applicable
· Upper:	Not applicable
· Flash point:	>100 °C
· Auto-ignition temperature:	Not determined
· Solubility	
· water:	Partly miscible.
· Vapour pressure:	Not determined.
· Relative density at 25 °C:	0.99
· Vapour density (air=1):	Not available
· Particle characteristics	Not applicable.

· **9.2 Other information**

· **9.2.1 Information with regard to physical hazard classes**

Not applicable

· **9.2.2 Other safety characteristics**

· Evaporation rate	Not available
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Solvent content:	
· Organic solvents:	Not available
· VOC (EC)	0.00 %

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

· **10.2 Chemical stability** Chemically stable at normal temperatures and pressures.

(Contd. on page 7)

—GB—

Safety data sheet

according to UK REACH

Page 7/12

Printing date 23.07.2025

Version number 1.00

Revision: 23.06.2025

Trade name: 832FXT-B

(Contd. of page 6)

- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:**
Strong acids
Strong oxidizing agents
- **10.6 Hazardous decomposition products:** Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
 - **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
ATE (Acute Toxicity Estimates)		
Oral	LD50	2,848 mg/kg
25620-58-0 trimethylhexane-1,6-diamine		
Oral	LD50	900 mg/kg (rat)
61788-46-3 Amines, coco alkyl		
Oral	LD50	500 mg/kg (ATE)
90-72-2 2,4,6-tris(dimethylaminomethyl)phenol		
Oral	LD50	500 mg/kg (ATE)

- **Primary irritant effect:**
 - **Skin corrosion/irritation** Causes severe skin burns and eye damage.
 - **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure**
May cause damage to the liver, the immune system and the gastro-intestinal tract through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Summary of Effects and Symptoms by Routes of Exposure**
 - **Eyes:** eye damage, pain
 - **Skin:**
rash, allergic contact dermatitis
chemical burns
 - **Inhalation:** may cause mild respiratory irritation
 - **Swallowed:**
May cause pain and corrosive burns to the mouth, throat, esophagus, and stomach.
drowsiness or dizziness

(Contd. on page 8)

— GB —

Safety data sheet

according to UK REACH

Page 8/12

Printing date 23.07.2025

Version number 1.00

Revision: 23.06.2025

Trade name: 832FXT-B

(Contd. of page 7)

- **Subacute to chronic toxicity:**
 - **Delayed and immediate effects as well as chronic effects from short and long-term exposure**
Prolonged or repeated exposure may cause skin allergies.

· 11.2 Information on other hazards

· Endocrine disrupting properties		
61788-44-1	phenol, styrenated	List II

SECTION 12: Ecological information

- **12.1 Toxicity**
 - **Aquatic toxicity:**
Very toxic to aquatic life with long lasting effect.
Avoid release to the environment.
Collect spillage.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
 - **Additional ecological information:**
 - **General notes:**
Must not reach sewage water or drainage ditch undiluted or unneutralised.
Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.

* SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
 - **Recommendation** This material and its container must be disposed of as hazardous waste.

· European waste catalogue	
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP8	Corrosive
HP13	Sensitising
HP14	Ecotoxic

- **Uncleaned packaging:**
 - **Recommendation:**
Containers may still present a chemical hazard/ danger when empty.
Dispose of contents in accordance with all local, regional, national, and international regulations.

(Contd. on page 9)

— GB —

Safety data sheet

according to UK REACH

Page 9/12

Printing date 23.07.2025

Version number 1.00

Revision: 23.06.2025

Trade name: 832FXT-B

(Contd. of page 8)
Where possible retain label warnings and SDS and observe all notices pertaining to the product.

SECTION 14: Transport information

14.1 UN number or ID number - ADR, IMDG, IATA	UN1760
14.2 UN proper shipping name - ADR, IMDG - IATA	CORROSIVE LIQUID, N.O.S. (Amines, coco alkyl, trimethylhexane-1,6-diamine) Corrosive liquid, n.o.s. (Amines, coco alkyl, trimethylhexane-1,6-diamine)
14.3 Transport hazard class(es) - ADR, IMDG, IATA  - Class - Label	8 Corrosive substances. 8
14.4 Packing group - ADR, IMDG, IATA	II
14.5 Environmental hazards: - Marine pollutant: - Special marking (ADR): - Special marking (IATA):	Product contains environmentally hazardous substances: Amines, coco alkyl MARINE POLLUTANT ENVIRONMENTALLY HAZARDOUS ENVIRONMENTALLY HAZARDOUS
14.6 Special precautions for user - Hazard identification number (Kemler code): - EMS Number: - Stowage Category - Stowage Code	Not applicable. 80 F-A,S-B B SW2 Clear of living quarters.
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:  Limited Quantity 832FXT-25ML, 832FXT-50ML, 832FXT-400ML	
- ADR - Limited quantities (LQ) - Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml

(Contd. on page 10)

—GB—

Safety data sheet

according to UK REACH

Page 10/12

Printing date 23.07.2025

Version number 1.00

Revision: 23.06.2025

Trade name: 832FXT-B

(Contd. of page 9)

· Transport category · Tunnel restriction code	Maximum net quantity per outer packaging: 500 ml 2 E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1760 CORROSIVE LIQUID, N.O.S. (AMINES, COCO ALKYL, TRIMETHYLHEXANE-1,6-DIAMINE), 8, II

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Poisons Act

· Regulated explosives precursors (Part 1)	None of the ingredients is listed.
· Regulated poisons (Part 2)	None of the ingredients is listed.
· Reportable explosives precursors (Part 3)	None of the ingredients is listed.
· Reportable poisons (Part 4)	None of the ingredients is listed.

Directive 2012/18/EU

- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category E1 Hazardous to the Aquatic Environment
- Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t

REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II	None of the ingredients is listed.
· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))	None of the ingredients is listed.
· Annex II - REPORTABLE EXPLOSIVES PRECURSORS	None of the ingredients is listed.
· Regulation (EC) No 273/2004 on drug precursors	None of the ingredients is listed.

(Contd. on page 11)

Safety data sheet

according to UK REACH

Page 11/12

Printing date 23.07.2025

Version number 1.00

Revision: 23.06.2025

Trade name: 832FXT-B

(Contd. of page 10)

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors
None of the ingredients is listed.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

· Classification according to Regulation (EC) No 1272/2008	
Skin corrosion/irritation Serious eye damage/irritation Skin sensitisation Specific target organ toxicity (repeated exposure) Hazardous to the aquatic environment - short-term (acute) aquatic hazard Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· **Department issuing SDS:** Regulatory department

· **Contact:** sds@mgchemicals.com

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
ATE: Acute toxicity estimate values
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

(Contd. on page 12)

Safety data sheet
according to UK REACH

Page 12/12

Printing date 23.07.2025

Version number 1.00

Revision: 23.06.2025

Trade name: 832FXT-B

(Contd. of page 11)

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**

— GB —